

Dry Film Dispenser

Mega Part No.27-22700

This dispenser has been designed to provide light safe storage and trouble free dispensing of dry film in a production environment. It is quick and easy to load, has a convenient storage facility for associated tools and incorporates an effective film measurement gauge.

Loading Film

In safe light conditions for the film carry out the following steps.

1/ Raise the lid so that it locks in the 'open' position.



2/ Gently pull outwards the locking ears on the lid sides so that they clear the lugs at each end of the clamp bar, and lift the lid further so that it comes to rest on its own over the back of the dispenser.



3/ Lift out the tray.



4/ Lift upwards both lugs of the clamp bar and direct rearwards so that the lugs rest on the steps thus latching the clamp uppermost in its open position.



5/ Remove the roll of film from the packing carton complete with the square end supports, remove the end supports to facilitate the removal of the black polythene sheet protecting the film, (retain the film information label holding this sheet in place for future reference). Replace the end supports and place the assembly directly into the dispenser so that the film will de-spool from the top of the roll.



6/ Gently remove the tape holding the film to the roll. Feed the full width of the film under the clamp bar. Unlatch the clamp bar so that the film is held in place.



7/ Place any moisture absorbing packets found in the packaging in the dispenser with the film, and replace the tray so that it sits on the roll supports.



8/ Refit lid in the 'open' position.

9/ Fit film gauge bar.



Operation

Film is drawn by hand across the indicators on the gauge when the clamping bar is raised by lifting the lid further with the other hand. When sufficient film is drawn the film can then be cut safely in the cutting channel in front of the automatic film clamp.



Note

When not in use, remove the gauge bar and place in the storage tray, then shut the lid.